

STUCCO Antico

NATURAL POLISHED PLASTER FINISH

Content:

| | | |
|----------|-----------------------------------|--------|
| 1 | STUCCO Antico overview |2 |
| | Suitable Surfaces |2 |
| | Main Characteristics |2 |
| | Application on absorbent surfaces |3 |
| | Transport & Storage |3 |
| | Consumption |3 |
| | Colours |3 |
| 2 | Application Guide |4 |
| 3 | Material Safety Data Sheet |5 |

WWW.BAUWERK.COM.AU

For further information, including colour charts, specific application procedures, products and workshops please refer to our website at www.bauwerk.com.au

STUCCO Antico

NATURAL POLISHED PLASTER FINISH

STUCCO Antico is a traditional lime based plaster finish suitable for external and internal wall application. It can be polished to a fine luster.

Suitable surfaces

- lime or cement rendered walls, inside and outside
- brickwork
- most natural stones
- cement sheeting
- fibre reinforced concrete
- plaster board
- historic houses
- bathrooms and high humidity environments

STUCCO Antico requires no undercoat or sealer and can be applied to new and old surfaces.

Main Characteristics

- not film forming, will not blister or peel
- simple application, easy redecoration
- 100% UV-stable
- completely permeable, will not lock moisture into walls
- non-flammable
- reduces surface stress due to heat reducing micro-crystals
- humidity regulating properties, improves micro-climate
- non-toxic, no fumes, free from VOC's
- safe for people with allergies or chemical sensitivity
- extremely long shelf life
- water based, easy clean up
- natural anti bacterial properties
- no electrostatic charge - will not attract dust
- long lasting

BAUWERK

Application on absorbent surfaces

- no undercoat required
- basic preparation of repair surface and clean off all loose particles
- can be applied as soon as surface is ready - no curing time needed
- can be applied into damp surfaces
- simple application with stainless steel trowel three coats
- material will bond with wall surface
- easy cleanup

Transport & Storage

- safe transport by road, rail, sea or air
- non-toxic, no explosive fumes, non-hazardous
- minimum shelf life 5 years in airtight containers

Consumption

1 square mtrs per kg of material on smooth substrate.
On rough/ uneven surface we recommend to apply a smooth render to lessen consumption of material.

Colours

BAUWERK uses artist-quality earthen and mineral pigments, which allow for the development of a comprehensive colour range, from natural earthy tones to bright modern colours, and result in a superior durable finish. Colours may be mixed to match existing features.

STUCCO Antico

NATURAL POLISHED PLASTER FINISH

APPLICATION GUIDE (including for use in Bathrooms)

1. allow for adequate waterproofing for all wet areas
2. prepare surface in similar manner as for tiling preparation
3. surface shall be free from loose, flaking or dusty materials, free from grease, form release oil or similar contaminants
4. if applied onto framed wall ensure adequate spacing of stud frames and thickness of waterproof boards; seal wall with approved waterproofing material, allow for bridging coat if surface is very smooth
5. if applied onto masonry surface dampen wall with fine mist spray or similar prior to application of first coat
6. apply covering whole sections using natural breaks and corners, do not stop at midway through one section
7. apply first coat (first coat will even out all imperfections)
8. apply second coat using stainless steel trowel (second coat provides body and smoothness)
9. apply third and final coat and polish surface to desired level of shine
10. allow to cure for a minimum of two weeks prior to use
11. curing will take place by atmospheric reaction with carbon dioxide. The surface will be soft initially, but harden to marble-like strength over a period of time
12. avoid all acids or harsh cleaning agents - we recommend to use Savon Noir to nourish and clean the surface (available from BAUWERK)

BAUWERK

MATERIAL SAFETY DATA SHEET for STUCCO Antico

1. IDENTIFICATION OF SUBSTANCE, MANUFACTURER & SUPPLIER:

Product Name: Stucco Antico
Product Type: lime base wall covering
Manufacturer: IMPEX s.r.l.
Address: Via G.Pascoli 23 - 31030Dossone di Casier, Italy

2. PRODUCT COMPOSITION

Content: Water, calcium hydroxide, calcium carbonate, binders

Dangerous Substances: No substances included that are listed as health risks under 677548/CEE

Labeling: Xi, irritant for eyes and skin

Handling: Lime is of alkaline nature and can break down the natural oils that protect the skin.
Wear eye protection. Use rubber gloves or barrier cream.
When in contact with eyes or skin wash with plenty of water, see doctor

First Aid: Skin: wash thoroughly with soap and water
Eyes: Wash thoroughly with water and rinse with boric acid solution
Ingestion: induce vomiting and seek medical attention

package sizes: 5 kg, 25 kg

Cleaning: normal protection for all areas not to be painted, clean brushes with mildly soapy water, use sand for spillage, wash with clean water, final cleaning with weak solution of vinegar

Spillage: use sand for spillage, wash with clean water

Disposal: allow water to evaporate, remaining cake can safely disposed of in normal household waste

Transport: non-hazardous product

Storage: frost free storage, shelf life 5 years in airtight container

Flammability: non-flammable

Incompatible Materials on contact with acid generates heat

Toxicity: non-toxic, does not contain substances with a particular toxicological relevance

issue 4/04

BAUWERK

271 SOUTH TERRACE, SOUTH FREMANTLE, WESTERN AUSTRALIA 6162

ABN 85942271079 TEL+61 (08) 9433 1008 FAX+61 (08) 9433 1009